WARNING SYSTEMS

FIREBALL® STROBE WARNING LIGHTS

- · Very bright and compact strobe light
- Emits a powerful "lightning bolt" flash of light
- Approximately 5" tall and 4" in diameter
- Rated at 300-effective candlepower, can be used in a variety of stationary and vehicular warning requirements
- · Available in 12-24 VDC, 120 VAC, and 240 VAC
- 10 000 hour strobe tube
- UL and cUL Listed, CSA Certified for indoor/outdoor use
- Type 4X, IP66 enclosure





FEDERAL SIGNAL CORPORATION

Model No.	Mfg. No.	Colour	Price/Each
XC135	FB2PST-120A	Amber	
XC136	FB2PST-120R	Red	
XC256	FB2PST-120B	Blue	
XC257	FB2PST-120C	Clear	
XC258	FB2PST-120G	Green	

STREAMLINE® LOW PROFILE LED LIGHTS

- 120 VAC
- 1/2" male pipe mount
- 100 000-hour LED lamp life
- Screw-on lens
- Type 4X enclosure
- Optional wire lens guard
- UL and cUL Listed,









FEDERAL SIGNAL CORPORATION

Model No.	Mfg. No.	Colour	Price/Each
XC420	LP3ML-120A	Amber	
XC421	LP3ML-120B	Blue	
XC422	LP3ML-120R	Red	
XC423	LP3ML-120C	Clear	
XC424	LP3ML-120G	Green	

Note: Also available in 24 VDC

BATTERY POWERED PORTABLE LED WARNING LIGHTS

- Portable, battery-powered LED warning light which flashes 50 times per minute
- Power is supplied by two standard 6VDC, spring terminal lantern batteries (not included)
- Type 3R weatherproof enclosure
- Magnetic mount
- 50 000-hour lamp life
- Voltage: 12 VDC





FEDERAL SIGNAL CORPORATION

Model No.	Mfg. No.	Colour	Price/Each
SG1636	BPL26L-R	Red	
SGI637	BPL26L-A	Amber	
SG1638	BPL26L-B	Blue	
SG1639	BPL26L-C	Clear	
SG1640	BPL26L-G	Green	

STREAMLINE® LOW PROFILE STROBE LIGHTS

- · Features a state-of-the-art strobe rated for 7000 hours
- High-quality, long-life strobe tubes are designed to reduce tungsten build-up for longer lamp maintenance cycles
- Screw-on lens provides easy access
- Low profile
- Available in 120VAC and 12-48VDC
- Type 4X, IP66
- UL and cUL Listed, CSA Certified
- · PLC and triac compatible





FEDERAL SIGNAL CORPORATION

Model No.	Mfg. No.	Description	Price/Each
XC125	LP3P-120A	Amber, Pipe Mount	
XC126	LP3P-120R	Red, Pipe Mount	
XC286	LP3P-120B	Blue, Pipe Mount	
XC287	LP3P-120C	Clear, Pipe Mount	
XC288	LP3P-120G	Green, Pipe Mount	
XC127	LP3T-012-048A	Amber, T Mount	
XC128	LP3T-012-048B	Blue, T Mount	
XC129	LP3T-012-048R	Red, T Mount	
XC289	LP3T-012-048C	Clear, T Mount	
XC290	LP3T-012-048G	Green, T Mount	
XC130	LP3E-120A	Amber, Edison Base	
XC131	LP3E-120R	Red, Edison Base	
XC262	LP3E-120B	Blue, Edison Base	
XC263	LP3E-120C	Clear, Edison Base	
XC264	LP3E-120G	Green, Edison Base	
XC132	LP3M-120A	Amber, Male Pipe Mount	
XC133	LP3M-120B	Blue, Male Pipe Mount	
XC134	LP3M-120R	Red, Male Pipe Mount	
XC265	LP3M-012-048B	Blue Male Pipe Mount	
XC266	LP3M-012-048C	Clear Male Pipe Mount	
XC267	LP3M-012-048G	Green Male Pipe Mount	

FLASHING COMBINATION AUDIBLE/VISUAL SIGNALS

- Features 100% polycarbonate housing rated for Type 3R rain-tight applications
- Surface mount, integrated 1/2" pipe mount and 4" electrical box mount
- Twist-off lens for easy access
- Internal buzzer produces 85 dB at 10'
- 120 VAC
- · UL and cUL Listed, CSA Certified
- · Type 3R enclosure





FEDERAL SIGNAL CORPORATION

Model No.	Mfg. No.	Description	Price/Each
XC119	AVIST-120A	Strobe Tube, Amber	
XC120	AVIST-120R	Strobe Tube, Red	
XC278	AV1ST-120B	Strobe Tube, Blue	
XC279	AV1ST-120C	Strobe Tube, Clear	
XC280	AV1ST-120G	Strobe Tube, Green	