MANUAL-CLOSING **MOLASSES GATE VALVES**

- Excellent for dispensing heavy oils, light grease, varnish, molasses, honey, cream and other non-flammable heavy viscous fluids from drums and containers
- All gates have 45-60° discharge for optimum flow control
- Durable cast iron body, painted black enamel finish
- Machined and lapped brass faceplate for smooth operation and perfect seal
- Can be padlocked in sizes up to and including 2"
- Standard gates come with either 2" or extra long 4" iron handle
- Extra long handle provides greater leverage for easier and safer dispensing of viscous fluids
- Gate valve with lock nut is used on drums with over-sized or damaged threads
- Malleable iron lock nut combined with rubber gasket allows valve to face any direction







Model No.	NPT Inlet Size"	Wt. lbs.	Price/Each
STANDARD	GATE WITH 2" HAND	LE	
DA059	3/4	1.5	
DA060	1	2.0	
DA061	1 1/4	2.4	
DA062	1 1/2	2.9	
DA063	2	3.2	
DA057	3	6.8	
DA058	4	15.5	
STANDARD GATE WITH 4" HANDLE			
DA055	1 1/2	4.3	
DA056	2	4.6	
DA054	3	7.7	
GATE VALVE WITH LOCK NUT, 2" HANDLE			
DA051	3/4	1.6	
DA052	1 1/2	3.2	
DA053	2	3.6	

Note: These faucets are intended for use with nonflammable viscous liquids stored in or dispensed from nonpressurized containers at ambient room temperature.

SELF-CLOSING FAUCETS

- For non-flammable liquids only
- No flame arrestor
- 3/4" pipe thread
- Can be padlocked closed
- Natural die cast finish

Model No. PE365 Price/Each \$





SELF-CLOSING FAUCETS W/SCREEN KLETON

- · Flame arrestor safety faucet Standard 3/4" tapered
- pipe thread
- Can be padlocked closed
- Natural die cast finish

Model No. PF364 Price/Fach \$



SELF CLOSING GATE VALVES For use with viscous non-corrosive fluids

- heavier than SAF30 motor oil
- Heavy-duty brass construction
- Self-closing PTFE blade has fast, positive shut off when handle is released
- 4 1/2" wide handle
- Wide opening permits maximum flow
- Fits 2" bung in steel or plastic drums
- Weight: 7 lbs.

Model No. PE363 Price/Each \$



MANUAL-CLOSING **POLY FAUCETS**

Ideal for use with non-flammable, often corrosive liquids

3/4

- Half turn on/off; stays open until shut-off
- Use 2" size for thick. viscous liquids or larger volume flow of thin liquid

Model

DA048

DA049



Type

Flo-King^e

Flo-Rite®

ŀΑ	U		ы	IS.
	_	_	_	•

- · Approved for use with oils, flammables and non-flammable
- Internal flame arrestor
- Teflon® gasket
- FM approved



DC404
DA043

Model No.	Material	NPT Inlet Size"	Price /Each
DC404	Brass	3/4	,
DA043	Stainless steel	3/4	

POLYETHYLENE DRUM FAUCETS

- Produced from FDA-approved material
- Includes 3 EPDM sealing gaskets: thin, medium, thick
- NPT Inlet Size: 2"



Model		Price
No.	Includes	/Each
DC630	-	
DC631	Level Gauge Port, Pail Hook	

Bonding and grounding wire assemblies dissipate the static electricity generated during the transfer of flammable liquids. Various clamp styles available to work with different containers. Required by OSHA for fluids with a flashpoint below 140°F.



COILED GROUNDING **CLAMPS**

- Vinyl coated 1/8" cable resists corrosive environments to give years of service
- Unit is self-coiling to retract when not in use



Model No.	Description	Price/Each
DA632	5' coil	
DA628	10' coil	
DA777	15' coil	
DB029	20' coil	
DA778	30' coil	

HEAVY-DUTY AVIATION STATIC GROUNDING HAND CLAMPS

- Aviation industry standard for bonding and grounding aircraft and refueling vehicles
- Ideal for attaching to landing gear, posts, ground balls, ground rods and other curved, unpainted surfaces
- Cast aluminum construction with plated steel jaws
- Clamp opens to 13/16" and can take up to #6 cable
- Weight: 0.3 lbs

Model No. DC488 Price/Each \$



HEAVY-DUTY HAND CLAMPS

- Grounding clamp for flammable drum loading
- Die cast aluminum body, stainless steel points and 55-lbs. spring enable clamp to consistently make positive metal to metal ground connection
- Accommodates all cable up to 5/32"; connection is made in clamp's handle held by dual Allen screw contacts

Model No. DA633 Price/Each \$

