

GAS WELDING OUTFITS & ACCESSORIES

BULK SINGLE LINE CORRUGATED WELDING HOSES, GRADE R

- **Green hose** is for oxygen
- **Red hose** is for acetylene use only, and where cover must resist abrasion, weather and ozone
- Heat resistant EPDM tube and cover
- Two spiral polyester yarn reinforcement, more flexible than braid reinforced hose, easier to coil and handle
- Conforms to RMA/CGA specifications
- Multi-ventilating pores disperses permeating gases, enhances welder's safety
- Working pressure: 200 PSI, 1.38 Mpa
- **Sold in full 700' reels, priced per foot**



HBD/Thermoid, Inc.

Model No.	Mfg. No.	Nominal I.D."	Nominal O.D."	Min. Bend Radius"	Price /Each
GREEN HOSES					
302-5005	00521803205	3/16	0.44	1.25	
302-5020	00521804205	1/4	0.53	1.50	
302-5070	00521806400	3/8	0.72	2.25	
RED HOSES					
302-5000	00521903205	3/16	0.44	1.25	
302-5015	00521904205	1/4	0.53	1.50	
302-5065	00521906400	3/8	0.72	2.25	

TULINE TWIN WELDING HOSE ASSEMBLIES

- Premium quality US made hose with "B" size brass fittings



HBD/Thermoid, Inc.

Model No.	Mfg. No.	Nominal I.D."	Length'	Price /Each
GRADE R HOSES				
PB087	00521403225	3/16	25	
PB090	00521484225	1/4	25	
PB091	00521484250	1/4	50	
PB092	00521484290	1/4	100	
PB094	00521405252	5/16	50	
PB095	00521405291	5/16	100	
302-1260	00521406251	3/8	50	
302-1270	00521406290	3/8	100	

Model No.	Mfg. No.	Nominal I.D."	Length'	Price /Each
GRADE T HOSES				
PB069	00521584225	1/4	25	
PB070	00521584250	1/4	50	
PB071	00521584290	1/4	100	
302-7170	00521586250	3/8	50	
302-7180	00521586290	3/8	100	

HOSE REPAIR KITS

- Special B-size kit offers 12 different items most frequently used for hose repair
 - Kit with C-5 crimp tool for 3/16" x 1/4" I.D. hose
 - Tough polyethylene case includes handy chart that identifies and describes fittings in each compartment
 - **Includes:**
 - Hose nuts & nipples
 - Splicers
 - Couplers
 - Ferrules
 - Crimping tool
- Model No. NP497
Mfg. No. CK-24
Price/Each \$



WESTERN ENTERPRISES

BULK TULINE TWIN WELDING HOSES, GRADE T

HBD/Thermoid, Inc.


- For use with all fuel gases and where a flame and oil resistant tube and cover are required
- CR (polychloroprene) tube and cover offers medium-high fuel gas resistance
- Two spiral polyester yarn reinforcement, more flexible than braid reinforced hose, easier to coil and handle
- Conforms to RMA/CGA specifications
- Multi-ventilating pores disperses permeating gases, enhances welder's safety
- Working pressure: 200 PSI, 1.38 Mpa
- **Sold in full 700' reels, priced per foot**



Model No.	Mfg. No.	Nominal I.D."	Nominal O.D."	Min. Bend Radius"	Price /Each
302-7010	00521504200	1/4	0.53	1.50	

BULK TULINE TWIN WELDING HOSES, GRADE R

- **Red hose** is for acetylene use only, and where cover must resist abrasion, weather and ozone
- Heat resistant EPDM tube and cover
- Two spiral polyester yarn reinforcement, more flexible than braid reinforced hose, easier to coil and handle
- Conforms to RMA/CGA specifications
- Multi-ventilating pores disperses permeating gases, enhances welder's safety
- Working pressure: 200 PSI, 1.38 Mpa
- **Sold in full 700' reels, priced per foot**



HBD/Thermoid, Inc.

Model No.	Mfg No.	Nominal I.D."	Nominal O.D."	Min. Bend Radius"	Price/Each
302-1000	00521403200	3/16	0.44	1.25	
302-1010	00521404200	1/4	0.53	1.50	
302-1020	00521405200	5/16	0.59	2.00	
302-1030	00521406200	3/8	0.66	2.25	

MIG/TIG INERT GAS HOSES

- Working pressure: 300 PSI
- Connection: 5/8" - 18 RH(M)
- I.D.: 1.4"
- Length: 6'
- Hose Inside Diameter: 1/4"



GENTEC
GENSTAR TECHNOLOGIES

Model No.	Mfg. No.	Price/Each
TTU563	HA14-0061N	

EMERGENCY WELDING HOSE REPAIR KITS

- **Plastic kit box contains:**
 - 1 Standard jaw pincers
 - 6 Oxygen "B" RH brass nuts
 - 6 Acetylene "LH" brass nuts
 - 6 1/4" brass nipples
 - 4 1/4" brass hose menders
 - 2 3/16" brass nipples
 - 2 3/16" brass hose menders
 - 10 1/2" 2-ear clamps
 - 40 9/16" 2-ear clamps
 - 4 9/16" twin clamps

Model No. NP512
Mfg. No. WK-82
Price/Each \$



OETIKER
Connecting Technology